



## Conductor connector



Item no. 172623



Item no. 172622

### Technical Data

No. of poles: 3  
 Clamp: screw  
 Cable diameter: max 1.5 mm<sup>2</sup>  
 Cable diameter min-max: 7 mm - 13.5 mm  
 Protection category: IP68 2 bar (20 m/1H)  
 Rated current and voltage: 32 A 250 V  
 Temperature range: -40°C to 125°C

### Technical Data

No. of poles: 3  
 Clamp: screw  
 Cable diameter: max 4 mm<sup>2</sup>  
 Cable diameter min-max: 7 mm - 10.5 mm  
 Protection category: IP68 2 bar (20 m/1H)  
 Rated current and voltage: 32 A 450 V  
 Temperature range: -40°C to +125°C



Item no. 168467



Item no. 180547

### Technical Data

No. of poles: 3  
 Clamp: screw  
 Cable diameter: max 4 mm<sup>2</sup>  
 Cable diameter min-max: 7 mm - 12 mm  
 Protection category: IP68 1 bar (10 m/1H)  
 Rated current and voltage: 32 A 450 V  
 Temperature range: -40°C to +125°C

### Technical Data

No. of poles: 5  
 Clamp: screw  
 Cable diameter: max 4 mm<sup>2</sup>  
 Cable diameter min-max: 7 mm - 13.5 mm  
 Protection category: IP68 5 bar (50 m/1H)  
 Rated current and voltage: 32 A 450 V  
 Temperature range: -40°C to +125°C



Item no. 198699

### Technical Data

No. of poles: 3  
 Clamp: Quickon-fast connection  
 Cable diameter: 0.5 mm<sup>2</sup> - 1.5 mm<sup>2</sup>  
 Cable diameter min-max: 5 mm - 9.5 mm  
 Protection category: IP68/69K (2 m/24 H)  
 Rated current and voltage: 17.5 A 690 V  
 Temperature range: -40°C to +100°C

Item no.	Designation
✓ 172623	TeeTube «Y-distributor 3p» for cable Ø 7-13.5 mm
✓ 172622	TeeTube «T-distributor 3p» for cable Ø 7-10.5 mm
✓ 168467	TeeTube «mini 3p» for cable Ø 7-12 mm
✓ 180547	TeeTube, 5p for cable Ø 7-13.5 mm
✓ 198699	Phoenix «connector 3p», quick connector for cable Ø 5-9.5 mm

✓ from stock, offer subject to prior sale